

ROTAX® ENGINE	600 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	40 liters
Oil tank capacity	2.1 liters

POWERTRAIN

Drive clutch type	eDrive
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.86:1
Large sprocket number of teeth	2nd gear = 2.3:1
Drive sprocket number of teeth	7
Brake system	Hydraulic brake with braided steel

brake line, plastic master cylinder

COLOUR

Red/Black

DIMENSIONS

Vehicle overall length	3250 mm
Vehicle overall width	1085 mm
Vehicle overall height	1430 mm
Ski stance	900 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	32 mm

SUSPENSION

Front suspension	LTS
Front shock	MC
Rear suspension	PPS-5900-A
Center shock	HPG 25
Rear shock	HPG 25

FEATURES

Frame	L-XU
Skis	Blade
Seating	1-up
Handlebar	Steel with hooks, 205 mm riser, mountain strap
Reverse	Mechanical (2F-N-R)

Heated grips	STD
Gauge	Analog with display
Electric start	STD
Mirrors	Accessory
Windshield	High (510 mm), one piece
Hitch	STD



©2016 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, ® and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.